

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 05-223674

(43)Date of publication of application : 31.08.1993

(51)Int.Cl.

G01L 13/02

(21)Application number : 04-029624

(71)Applicant : YOKOGAWA ELECTRIC CORP

(22)Date of filing : 17.02.1992

(72)Inventor : MIYAUCHI TATSUHIKO
MIYASHITA TAKASHI


(54) DIFFERENTIAL PRESSURE TRANSMITTER

(57)Abstract:

PURPOSE: To reduce the span variation due to the variation of an ambient temperature by making the rates of the variation of hardness of a center diaphragm and a seal diaphragm roughly equal.

CONSTITUTION: The materials of a center diaphragm 7 and a seal diaphragm 12, 13 are respectively set such materials that both rates of the variation of hardness per the variation of an ambient temperature are roughly equal. The pressure H_z that acts to the high pressure side and the pressure P_L that acts to the low pressure side, individually act the diaphragms 12, 13 and surfaces of silicon diaphragm 8 respectively via sealed liquids 101, 102 so that the diaphragm 8 bends. The bend is detected by a strain gauge 80 and the differential

pressure is converted to an electric signal to be output therefrom. At this time the diaphragm is deformed to the low pressure side, thereby the movement of the sealed liquids of 101, 102 due to the differential pressure are absorbed. Therefore, it is possible to reduce span errors when the rates of variation of hardness of the diaphragms of 7, 12, 13 are roughly equal.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]